

Wall mounted unit

ATXN-NB



Siesta



Comfortable sleeping mode



Vertical auto swing



24 hour timer

Siesta wall mounted unit, offering good value for money and ensuring a steady supply of clean air

- › Seasonal efficiency values up to A+
- › Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- › 24 hour timer can be set to start heating or cooling anytime during a 24 hour period

ATXN-NB + ARXN-NB



Indoor unit			ATXN	25NB	35NB	50NB	60NB
Casing	Colour		White				
Dimensions	Unit	HeightxWidthxDepth	288x859x209			310x1,124x237	
Sound power level	Cooling/Heating		53/53		54/54	55/55	61/61
Sound pressure level	Cooling	Super high/High/Nom./Low/Silent operation	41/40/34/29/21		42/41/34/30/22	44/40/38/35/32	46/43/41/37/33
	Heating	Super high/High/Nom./Low/Silent operation	41/40/34/29/21		42/41/34/30/22	44/40/38/35/32	46/43/41/37/33

Efficiency data			ATXN + ARXN	25NB + 25NB	35NB + 35NB	50NB + 50NB	60NB + 60NB
Cooling capacity	Min./Nom./Max.		kW	1.300/2.560/3.000	1.300/3.410/3.800	1.630/5.480/6.200	1.750/6.230/6.500
Heating capacity	Min./Nom./Max.		kW	1.300/2.840/4.000	1.300/3.580/4.750	1.170/5.620/6.600	1.200/6.400/8.000
Power input	Cooling	Min./Nom./Max.	kW	0.280/0.693/0.990	0.290/1.060/1.390	0.290/1.668/2.000	0.280/1.931/2.000
	Heating	Min./Nom./Max.	kW	0.260/0.700/1.100	0.285/0.950/1.480	0.240/1.550/2.510	0.240/1.680/2.000
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+			
		Pdesign	kW	2.56	3.41	5.48	6.23
		SEER		5.66	5.86	5.79	5.96
	Annual energy consumption	kWh	159	204	331	366	
	Heating (Average climate)	Energy label		A+			
		Pdesign	kW	2.41	2.80	3.37	3.80
SCOP			4.00		4.01	4.06	
Annual energy consumption	kWh	842	981	1,177	1,310		
Nominal efficiency	EER		3.69	3.22	3.29	3.23	
	COP		4.06	3.77	3.63	3.81	
	Annual energy consumption	kWh	347	530	833	964	
	Energy label	Cooling/Heating	A/A				

Outdoor unit			ARXN	25NB	35NB	50NB	60NB
Dimensions	Unit	HeightxWidthxDepth	mm	550x658x289		628x855x328	753x855x328
Sound power level	Cooling		dBA	58	60	64	65
	Heating		dBA	58	60	64	65
Sound pressure level	Cooling	Nom.	dBA	45	46	51	
	Heating	Nom.	dBA	45	46	51	
Operation range	Cooling	Ambient	Min.-Max.	10~46		-10~46	
	Heating	Ambient	Min.-Max.	-15~18			
Refrigerant	Type/GWP			R-410A/2,087.5			
	Charge		kg/TCO _{eq}	0.74/1.5	1.00/2.1	1.25/2.6	1.45/3.0
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/220-240			

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-038

04/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.